HANDICAP PARKING SIGN SPACE (FTP-25) 5' CONC. WALK FLUSH W/ ASPHALT BLUE 20' (TYP.) (INTERIOR) **STRIPING** 4" WHITE STRIPE 1101 EAST FIRST STREET SANFORD, FLORIDA 32771 (407) 321-1130 DEVELOPMENT 50:1 (TYP.) 5' 12' NOTE PARKING STALLS SHALL BE MARKED WITH WHITE REVIEW & BLUE PAINT PER FLORIDA ACCESSIBILITY CODE **SECTION 4.6.1. \$100 FINE** PARKING DISABLE PER MIT 318.14

NOTE:

ACCESSIBILITY: A) IN ACCORDANCE WITH THE FLORIDA ACCESSIBILITY CODE FOR BUILDING CONSTRUCTION, 4.1.3 SECTION (1), DATED OCT. 1996, AT LEAST ONE ACCESSIBLE ROUTE COMPLYING WITH 4.3 SHALL CONNECT ACCESSIBLE BUILDING OR FACILITY ENTRANCES WITH ALL ACCESSIBLE SPACES AND ELEMENTS WITHIN THE BUILDING OR FACILITY. DOORS ACCESSING THE BUILDING MUST BE DEPICTED ON SITE PLAN. RAMP DETAILS WITH SLOPE INFORMATION SHALL BE DEPICTED ON SITE PLAN. B) THE LOCATION OF HANDICAPPED PARKING STALLS, LOADING ZONES, SIDEWALKS AND RAMPS ON SITE SHALL MEET CHAPTER 316.1955 OF THE FLORIDA STATUES AND SECTION 4.1.3 OF THE FLORIDA ACCESSIBILITY CODE. CURB RAMPS SHALL NOT EXCEED 12:1 SLOPES PARKING SPACE AND AISLE SHALL NOT EXCEED 50:1 CROSS-SLOPE. (TLO 11-26-96) 12-11-96

NOTE: (HANDICAP SIGN ONLY)

- ALL LETTERS SHALL BE BLACK AND SHALL CONFORM TO FDOT "ROADWAY AND TRAFFIC DESIGN STANDARDS".
- TOP PORTION OF SIGN SHALL HAVE REFLECTORIZED (ENGINEERING GRADE) BLUE BACKGROUND WITH WHITE REFLECTORIZED LEGEND AND BORDER.
- 3. BOTTOM PORTION OF SIGN SHALL HAVE A REFLECTORIZED (ENGINEERING GRADE) WHITE BACKGROUND WITH BLACK BORDER.
- 4. ONE SIGN REQUIRED FOR EACH PARKING SPACE.
- HEIGHT OF SIGN SHALL BE 7' ABOVE GROUND IN ACCORDANCE WITH FDOT "ROADWAY AND TRAFFIC DESIGN STANDARDS".

HANDICAP RAMP AND PARKING STALL DETAIL